

LTE05UW-Sx-BU

Switching AC/DC USB Version

Main Features:

- Meet efficiency DoE VI & ErP CoC V5. Tier II
- Output Power up to 5W
- US Wall-Mount USB power supply

Technical Specification:

Input and Output Specification:

	S1(USB)
Input Voltage	90-264 Vac
Frequency	50 / 60Hz
Input Current	@115Vac 0.4Arms; @230Vac 0.25Arms
Inrush Current	No components damaged
Output Voltage	5V
Min Load	0A
Max Load	1 A
Output Power	5W
Line Regulation	±1.0%
Load Regulation	± 5%
Ripple & Noise (mVp-p)	250
Efficiency@115V/@230V	>68%; >68%

Note: 1.Load regulation is tested at 10% to 100% of rated load.

Note: 2.Peak-to-peak for 5W(convection rating)@115Vac MIN.; Measurements with a 20MHz bandwidth and terminated with a 10uF electrolytic Cap.in parallel with a 0.1uf ceramic Cap.

Environment Specification:

Operating Temperature:0-40℃

Storage Temperature:-40 to 85 ℃

Storage Humidity:5% to 95% RH

Safety and EMC Approval:

ITE: UL. BSMI. FCC . CB

Mechanical Specification:

Dimensions:

US PLUG: 47.9*27.8*26.5(mm)



Protection Specification:

Over Voltage Protection : Auto-Recovery

Over Load protection : Hiccup/Auto-Recovery

Short Circuit Protection:Hiccup/Auto-Recovery

Mechanical Drawing:

